



Marinite® FT

Live Fire Training Panels

Class A/B Burn Room Products

Marinite® I and the most recent version **Marinite FT** have been installed in burn room applications worldwide for more than 40 years. **Marinite FT's** high strength and dimensional stability have a proven performance record in Class "A" and fire simulator burn rooms. **Marinite FT** is UL® Listed to assure the highest quality and performance.

Marinite FT is specifically engineered for the most realistic live fire training, low specific heat; emissivity and likeness to common wall and ceiling construction materials.



PALM BAY FIRE TRAINING



PALM BAY FIRE RESCUE

Panel Sizes:

- 1" x 2' x 2'
- 1" x 2' x 4'
- 1" x 3' x 4'
- 1" x 4' x 4'

Custom sizes available upon request.

Physical Properties:

Modulus of Rupture (MOR)	3200 psi
Dry Density	75 pcf
Shrinkage — 24 hrs @ 1000°F	
Thickness	0.7%
Length	0.1%
Width	0.1%
Shrinkage — 24 hrs @ 1350°F	
Thickness	1.0%
Length	0.1%
Width	0.1%

Sold exclusively through **Armil CFS, Inc.**



UNDERWRITERS LABORATORIES INC.
CHICAGO • NORTHBROOK, ILL. • MELVILLE, N.Y. • SANTA CLARA, CALIF.

an independent, not-for-profit organization testing for public safety

Whether specifying a new training facility or replacing existing panels, **Marinite FT** is the proven first choice for live training burn rooms. Each panel is treated with a proprietary water repellent and ready for immediate installation and service.

Tough enough to withstand intense hose streams and impact in the extreme training environment.



Armil CFS, Inc.

15660 La Salle Street, South Holland, IL 60473
708-339-6810 office • 708-339-0517 fax
email: info@armilcfs.com
www.armilcfs.com

© 2023, Armil CFS, Inc.

