

KASK INTRODUCES NEW PRIMERO SERIES HELMETS FOR U.S. AND CANADIAN MARKETS.

ADVANCED HEAD PROTECTION FOR EVERYONE - EVERYWHERE.

TECHNICAL DETAILS

The new Primero series is the results of the holistic KASK commitment to safety, comfort and design. **Safety** is ensured thanks to a High Density Polypropylene external shell that decreases the helmet weight while increasing its protective abilities – **great impact resistance and high penetration protection.** The High Density Expanded Polystyrene inner shell guarantees all-around **high impact energy absorption** and improved comfort. As every KASK helmet, Primero is tested for rotational impact performance.

Exceptional wearer comfort is provided by an inner padding made of a quick-drying fabric with moisture-wicking technology that accelerates the dispersion of sweat to the surface of the helmet padding for keeping workers cool and dry. It can be easily removed or replaced via a patented Click-In system.

Moreover, Primero is designed with 14 air intakes shaped to prevent debris entry and internal channels for enhanced breathability. In addition, the **Ergo Fit System** allows for an easy and secure fit by turning the large diameter dial. The system moves up and down to adapt to a range of head shapes and the ergonomically shaped wings cradle the back of the neck for a secure fit. An advanced chinstrap in eco-leather with 5 adjustment points ensures a personalized fit and accommodates wider head sizes and adapts to earmuff use.

As with all KASK helmets, the **Primero features a number of additional design elements that enhance the wearer experience**. It is designed with integrated slots for easy mounting of KASK eye, face and hearing protection accessories and with front attachment point for advanced customization and easy integration of accessories such as badge holders and headlamps.

CLICK HERE TO LEARN MORE











MATERIAL

EXTERNAL SHELL: HD Polypropylene

INTERNAL SHELL: HD Expanded Polystyrene

HEADBAND: Soft PA Nylon



SIZE

One size fits most



WEIGHT 0.97 lb



STANDARD

ANSI Z89.1 TYPE I - CLASS E HT LT EN 12492

Protection against side, front and rear impacts Shock energy absorption capacity (Clauses 4.2.1.2 - front, 4.2.1.3 - lateral, 4.2.1.4 - rear) Penetration (Clause 4.2.2) Retention system strength (Clause 4.2.3) Retention system effectiveness (Clause 4.2.4)



TEMPERATURE OF USE

-22°F / +140°F



WHE00117

201	202	203	204
208	210	215	

TECHNOLOGIES

- **ERGO FIT SYSTEM** Moves up and down and cradles back of neck for a secure fit.
- > 2DRY LINER Moisture-wicking fabric technology for all-day comfort.
- **CLICK-IN SYSTEM** Attachment system that lets padding easily snap in and out.
- **ADVANCED LITE CHINSTRAP** 5 adjustment points and EN color-coded fastener.
- > RING TO HOOK Chinstrap loop that securely attaches helmet to a harness.
- **EASY CLICK SYSTEM** Integrated slots for eye and face protection. Adapters required.
- **EARMUFF ATTACHMENT SLOTS** 30 mm EURO slots for attaching earmuffs.
- > REPLACEABLE LAMP CLIPS 4 removable nylon lamp attachment clips.

DISCOVER MORE













ADVANCED **HEAD PROTECTION** MADE EASY.



PRIMERO AIR



MATERIAL

EXTERNAL SHELL: HD Polypropylene

INTERNAL SHELL: HD Expanded Polystyrene

HEADBAND: Soft PA Nylon



SIZE

One size fits most



WEIGHT 0.97 lb



STANDARD

ANSI Z89.1 TYPE I - CLASS C HT LT EN 12492

Protection against side, front and rear impacts Shock energy absorption capacity (Clauses 4.2.1.2 - front, 4.2.1.3 - lateral, 4.2.1.4 - rear) Penetration (Clause 4.2.2) Retention system strength (Clause 4.2.3) Retention system effectiveness (Clause 4.2.4)



TEMPERATURE OF USE

-22°F / +140°F

TECHNOLOGIES

- **VENTILATION CHANNELS** 14 air intakes shaped for preventing debris entry.
- **ERGO FIT SYSTEM** Moves up and down and cradles back of neck for a secure fit.
- **2DRY LINER** Moisture-wicking fabric technology for all-day comfort.
- **CLICK-IN SYSTEM** Attachment system that lets padding easily snap in and out.
- **ADVANCED LITE CHINSTRAP** 5 adjustment points and EN color-coded fastener.
- > RING TO HOOK Chinstrap loop that securely attaches helmet to a harness.
- **EASY CLICK SYSTEM** Integrated slots for eye and face protection. Adapters required.
- **EARMUFF ATTACHMENT SLOTS** 30 mm EURO slots for attaching earmuffs.
- > REPLACEABLE LAMP CLIPS 4 removable nylon lamp attachment clips.



WHE00119

201	202	203	204
208	210	215	

DISCOVER MORE



SCAN FOR COMPLETE

COLLECTION













MATERIAL

EXTERNAL SHELL: HD Polypropylene

INTERNAL SHELL: HD Expanded Polystyrene

HEADBAND: Soft PA Nylon



SIZE

One size fits most



WEIGHT

430 g



STANDARD

CSA Z94.1 TYPE I - CLASS E EN 12492

Protection against side, front and rear impacts Shock energy absorption capacity (Clauses 4.2.1.2 - front, 4.2.1.3 - lateral, 4.2.1.4 - rear) Penetration (Clause 4.2.2) Retention system strength (Clause 4.2.3) Retention system effectiveness (Clause 4.2.4)



TEMPERATURE OF USE

-30°C / +50°C



WHE00121

201	202	203	204
208	210	215	

TECHNOLOGIES

- **ERGO FIT SYSTEM** Moves up and down and cradles back of neck for a secure fit.
- > 2DRY LINER Moisture-wicking fabric technology for all-day comfort.
- **CLICK-IN SYSTEM** Attachment system that lets padding easily snap in and out.
- **ADVANCED LITE CHINSTRAP** 5 adjustment points and EN color-coded fastener.
- > RING TO HOOK Chinstrap loop that securely attaches helmet to a harness.
- **EASY CLICK SYSTEM** Integrated slots for eye and face protection. Adapters required.
- **EARMUFF ATTACHMENT SLOTS** 30mm EURO slots for attaching earmuffs.
- **REPLACEABLE LAMP CLIPS** 4 removable nylon lamp attachment clips.

DISCOVER MORE



SCAN FOR

COMPLETE

COLLECTION









ADVANCED **HEAD PROTECTION** MADE EASY.



PRIMERO AIR



MATERIAL

EXTERNAL SHELL: HD Polypropylene

INTERNAL SHELL: HD Expanded Polystyrene

HEADBAND: Soft PA Nylon



SIZE

One size fits most



WEIGHT

430 g



STANDARD

CSA Z94.1 TYPE I - CLASS C EN 12492

Protection against side, front and rear impacts Shock energy absorption capacity (Clauses 4.2.1.2 - front, 4.2.1.3 - lateral, 4.2.1.4 - rear) Penetration (Clause 4.2.2) Retention system strength (Clause 4.2.3) Retention system effectiveness (Clause 4.2.4)



TEMPERATURE OF USE

-30°C / +50°C

TECHNOLOGIES

- **VENTILATION CHANNELS** 14 air intakes shaped for preventing debris entry.
- **ERGO FIT SYSTEM** Moves up and down and cradles back of neck for a secure fit.
- **2DRY LINER** Moisture-wicking fabric technology for all-day comfort.
- **CLICK-IN SYSTEM** Attachment system that lets padding easily snap in and out.
- **ADVANCED LITE CHINSTRAP** 5 adjustment points and EN color-coded fastener.
- > RING TO HOOK Chinstrap loop that securely attaches helmet to a harness.
- **EASY CLICK SYSTEM** Integrated slots for eye and face protection. Adapters required.
- **EARMUFF ATTACHMENT SLOTS** 30mm EURO slots for attaching earmuffs.
- > REPLACEABLE LAMP CLIPS 4 removable nylon lamp attachment clips.



WHE00123

201	202	203	204	
208	2 10	215		

DISCOVER MORE



SCAN FOR COMPLETE COLLECTION







