

SE

SimpleSeal Shallow Plenum Luminaire

Budget Friendly CSSGI Series: Minimum Profile, Maximum Features

ISO 5-8

Suitable for
ISO 5-8 Spaces

SEALED ENCLOSURE



SimpleSeal CSSGI Series

- Delivered lumen range: 2,197 – 8,639 lm
- Input power: 23 – 69W
- Efficacy: 97 – 132 lm/W
- Suitable for ISO 5-8 cleanrooms and clean spaces
- Low profile design minimizes intrusion into the plenum space

Nominal sizes:	2'x2', 2'x4'
Installation type:	Grid
Lamp type:	LED

With the introduction of the **SimpleSeal™ CSSGI**, Kenall now offers a product suitable for **ISO 5-8 spaces**, ideal for a wide range of needs in cleanroom/clean space environments. Featuring an edge-lit light engine, the design allows for minimal intrusion into the plenum space (<2.0" depth) without compromising uniform lighting across the lens surface.

The CSSGI was designed with access to the internal housing and driver when installed, making it a more serviceable fixture than the competition.

The CSSGI is also available in a *Buy American Act* Compliant version. Designed with budgets in mind, this luminaire is ideal for clean spaces including laboratories, food processing plants, pharmacies and pharmaceutical manufacturing, research centers and more.



www.kenall.com | P: 800-4-Kenall | F: 262-891-9700 | 10200 55th Street Kenosha, Wisconsin 53144, USA
 It may be covered by patents found at www.kenall.com/patents. Content of specification sheets is subject to change; please consult www.kenall.com for current product details.
 ©2023 Kenall Mfg. Co.

A brand of **legrand**