

L-STOP



LOCOMOTIVE STOP SYSTEM

HIGHLIGHTS

- Lightweight wireless locomotive stop system that increases yard worker safety
- Includes a handheld transmitter, receiver, antenna and emergency stop
- Standalone wireless solution for all locomotives that can be easily integrated and removed from daily operations
- Fail-safe design for loss of communication, loss of power, broken wire or failed hardware - all result in safely stopping the locomotive

FEATURES

- Up to three handheld transmitters can be paired to a system
- Lockable power and pneumatic connections
- Pneumatic interface commands the locomotive stop
- Continuous signal monitoring
- Generator field isolation for redundancy
- Easy installation in under two hours
- Works on locomotives with or without locomotive remote control systems
- Works with competitive remote control systems
- External antenna for one-mile line-of-sight operating range
- Automatic horn and bell activation upon receiver braking due to the L-Stop is highly recommended to alert yard personnel. This feature is only available with systems that include horn and bell operation.
- Repeaters can be added to extend the operating range

CONFIGURATIONS

- Basic stop system
- Basic stop system plus electric horn and bell functionality
- Basic stop system plus pneumatic horn and bell functionality

COMPLIANCE

- United States (FCC) McQ-XBPSX
- Canada (IC) 1846A-XBPSX
- Brazil ANATEL 05774-16-01209
- Australia RCM





TECHNICAL DATA AND SPECIFICATIONS

ELECTRONIC DATA	
Response Time	Beacon rate .5 sec
Battery	OCU: Internal 3.7V 2000 mAh rechargeable Li-Ion. Recharges via micro-USB MCU: DC option, 64 VDC
OCU Battery Life	Eight to nine hours of continuous operation. Sleep mode of approx. 45 days

RF	
Frequency Range	900 MHz spread spectrum
Operating Range	One-mile line-of-sight Extended range options available with repeaters
RF Network	Eight independent network frequencies
Antenna	External

ACCESSORIES	
Repeaters	Site survey available on request

MECHANICAL DATA	
Weight	OCU: .75 lbs (0.34 kg) MCU: 2.11 lbs (0.96 kg) MCU w/Comp:12 lbs (5.44 kg)
Dimensions W x H x D	OCU: 4 x 4 x 1.5in (101.6 x 101.6 x 38.1mm) MCU: 13.5 x 11.75 x 6.5 in (342.9 x 298.5 x 167.6mm)
Housing	OCU: aluminum frame, ABS plastic with integrated display MCU: NEMA 4 fiberglass, hinged lockable lid
IP Rating	OCU: IP40-rated MCU: IP55-rated
Operating Temperature	-40° to +185°F (-40° to +85° C)

OPERATION AND INDICATION	
Transmitter	One e-stop Four auxiliary membrane pushbuttons
Receiver	Two safety stop outputs (standard) Two auxiliary outputs (configurable)

North America: +1.234.806.0018 | Sales.US@Cattron.com

Europe: +49.2151.4795.0 | Sales.EU@Cattron.com

UK: +44.1932.238121 | Sales.UK@Cattron.com

South America: +55.19.3518.7030 | Sales.BR@Cattron.com

Asia: Sales.CN@Cattron.com

Oceania: Sales.AU@Cattron.com

cattron.com

EN-2024-03-V1

Cattron™ reserves the right to change specifications and product details on this datasheet without prior notice. Cattron and all associated logos or marks are trademarks of Cattron and its subsidiaries. All rights reserved.