

MUSCA 2S

TYRO[™]

ELEVATED CONTROL. COMPACT SIZE.

The Musca 2S is your go-to solution for industrial remote control of straightforward applications in the transportation and industry sectors. Whether operating a winch, pump or generator, the handheld transmitter stands out as one of the best-selling remote controls, known for its multi-functionality and reliability.

The Musca 2S transmitter is a versatile and user-friendly solution for use in challenging conditions that require precise control to deliver exceptional performance.



KEY FEATURES

- IP67 waterproof housing
- High-quality keypad provides a sound and tactile click
- Works anytime, even in the dark, with backlit keys
- Durable construction made of impact-resistant TPE rubber
- User-friendly, ergonomic design for ease of use
- Multiple handheld transmitters per receiver are possible
- Powered by two AA alkaline batteries

OPTIONS

- Keypad (2-6 buttons)
- Custom icon on keypad
- Selectable key function (momentary/latching)
- Private label possibilities

ACCESSORIES

- Lanyard



TYRO™ MUSCA 2S

TECHNICAL SPECIFICATIONS

FREQUENCY (+HOPPING PROTOCOL)	2.4GHz (FHSS)
ANTENNA	Integrated
COMMUNICATION MODE	Duplex
TRANSMISSION POWER	10.0 dBm at 2.4 GHz (default)
REACTION TIME	Approx. 0.1 second
RECEIVERS PER TRANSMITTER	2.4 GHz: Max. 8 receivers
CERTIFICATION	CE, FCC, ISED, RCM, RED, ECE-R10
DEGREE OF PROTECTION	IP67
TEMPERATURE RANGE	-30° to +60°C (-22° to +140°F)
NUMBER OF FUNCTION BUTTONS	Keypad with 2-6 keys (optional customer specific)
BATTERY TYPE	Two 1.5V AA alkaline (non-rechargeable)
OPERATING TIME	Approx. 6 months (depending on usage)
DIMENSIONS (MM)	117.3 x 61.3 x 28.6 mm
DIMENSIONS (INCHES)	4.61 x 2.41 x 1.13 inches
WEIGHT	148 gram (0.32 lbs)

Visit cattron.com for more information.

Cattron™ reserves the right to change specifications and product details on this datasheet without prior notice. Cattron and all associated logos or marks are trademarks of Cattron and its subsidiaries. All rights reserved. [EN-06-2024-V1](#)



CONNECT. CONTROL. PROTECT.