

TRUSTED, TOUCHLESS HAND DRYING SOLUTIONS



XLERATOReco®

High Speed. No Heat.
500 Watts.

XLERATOR®

Original. Patented.
Still The Best.

ThinAir®

Surface Mounted.
Slimmer Profile.

XLERATORsync®

Sink Mounted.
Elevated User Experience.

CUSTOM COVERS



ENHANCED FEATURES



Available with
Electrostatic HEPA (eHEPA®)
Filtration System



Adjustable Speed and
Sound Control



Multi-Voltage Options:
110-120V Or 208-277V



Adjustable Heat Settings -
High, Medium, Low & Off



Externally Visible
Service LED

BENEFITS OF EXCEL'S HIGH-SPEED, ENERGY-EFFICIENT HAND DRYERS

- ✓ Touchless, Hygienic Hand Drying Solution
- ✓ 95% Cost Savings Vs. Paper Towels
- ✓ Made In USA® Certified
- ✓ Reduces Restroom Maintenance, Freeing Up Maintenance Staff
- ✓ Reduces Carbon Footprint of Hand Drying up to 94%
- ✓ 80% Less Energy Than Conventional Hand Dryers

**XLERATOR****ORIGINAL. PATENTED. STILL THE BEST.**

- ✓ Reliable, A Workhorse!
- ✓ 7-Year Limited Warranty
- ✓ Wattage: 1,490W (Heat On) - 425W (Heat Off)

**XLERATOReco****HIGH SPEED. NO HEAT. 500 WATTS.**

- ✓ Innovative No Heat Technology
- ✓ 7-Year Limited Warranty
- ✓ Wattage: 425W-530W - Install Multiple Units On One Circuit

**ThinAir****SURFACE MOUNTED. SLIMMER PROFILE.**

- ✓ Meets Accessibility Standards
- ✓ 5-Year Limited Warranty
- ✓ Wattage: 950 Watts (Heat On) - 300 Watts (Heat Off)


**XLERATORsync****SINK MOUNTED. ELEVATED USER EXPERIENCE.**

- ✓ Meets Accessibility Standards
- ✓ 7-Year Warranty
- ✓ Wattage: 1,440 Watts

FEATURES	XLERATOR			XLERATOReco			ThinAir			XLERATORsync		
DRY TIME	8 Seconds			10 Seconds			14 Seconds			14 Seconds		
ENERGY USE	3.7 Wh ¹			1.7 Wh ¹			3.7 Wh ¹			3.7 Wh ¹		
ADJUSTABLE SOUND	65 - 75 dB			65 - 75 dB			69 - 73 dB			68 - 75 dB		
WATTS	1,490W (Heat On), 425W (Heat Off)			425W-530W			950W (Heat On), 300W (Heat Off)			1,440W		
VOLTS / AMPS	110-120V 208-277V 230V	11.3-12.2A 5.6-6.2A 6.1A	60Hz 60Hz 50Hz	110-120V 208-277V 230V	4.3-4.5A 2-2.2A 2.2A	60Hz 60Hz 50Hz	110-120V 208-277V 230V	.2-7.8A 3.6-4A 3.9A	60Hz 60Hz 50Hz	110-120V 208-240V 230V	11.3-12.2A 5.6-6.6A 6.1A	50/60Hz 50Hz 50Hz
CUSTOM COVERS	✓			✓			✓			✓		
ELECTROSTATIC HEPA (eHEPA®) FILTRATION	Washable Pre-Filter Optional Electrostatic HEPA (eHEPA®) Filtration System			Washable Pre-Filter Optional Electrostatic HEPA (eHEPA®) Filtration System			Washable Pre-Filter Optional Electrostatic HEPA (eHEPA®) Filtration System			Washable Pre-Filter Electrostatic HEPA (eHEPA®) Filtration System		
MADE IN USA	✓			✓			✓			✓		



Smart EPD® verifies Environmental Product Declarations (EPDs) for consistency with the LCA and conformance with global Product Category Rules (PCR) for hand dryers. UL Environment published the first global PCR for hand dryers. Third-party testing to these guidelines documents a product's environmental impact over its lifecycle. This impact is detailed in Environmental Product Declarations, enabling specifiers and buyers to make true apples-to-apples comparisons and more informed product selections. Excel Dryer received the industry's first certified EPDs.

**ACCESSORIES & OPTIONS**

- ✓ 1.1" Noise Reduction Nozzle
- ✓ Electrostatic HEPA (eHEPA®) Filtration System
- ✓ Recess Kit
- ✓ Antimicrobial Wall Guards
- ✓ Custom Covers
- ✓ XChanger® Paper Towel Dispenser Retrofit Kit

¹Dry time and energy use testing performed by SGS International on standard XLERATOR/XLERATOReco Hand Dryers with 0.8" nozzle/standard ThinAir Hand Dryers to 0.25g or less of residual moisture, pursuant to the UL Environment Global Product Category Rules (PCR) for Hand Dryers.



TIME TO THROW IN THE TOWEL®

EXCEL DRYER INC • 1.800.255.9235 • EXCELDRYER.COM

**JULY
2025**

EDS2424775.1